



5.188 Inch | 131.775 Millimeter x 2.7500 in x 26.7500 in TIMKEN SDAF 22630 Pillow Block Bearings

Bearing No. SDAF 22630

SDAF 22630 Bearing 2D drawings and 3D CAD models

|                           |  |
|---------------------------|--|
| Category                  | Pillow Block Bearings  |
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 179.33   |
| EAN                       | 0087796311343  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Tapered Adapter Sleeve   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1-1/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22330K   |
| Seals                     | Triple Ring Labyrinth  |
| Housing Configuration     | 2 Piece Split  |
| Inch - Metric             | Inch   |
| Other Features            | Double Row   Heavy Duty  |
| Long Description          | 4 Bolt Pillow Block; 5-3/16" Bore; 7-1/2" Base to Center Height; Tapered Adapter Sleeve Mount; Spherical Roller Bearing; 20-7/8" Minimum Bolt Spacing; |



# LUOYANG MONTON BEARING SCIENCE & TECH...

|                                  |   |
|----------------------------------|---|
|                                  | 23-5/8" Bolt Spacing<br>Maximum;                          |
| Category                         | Pillow Block  |
| UNSPSC                           | 31171511  |
| Harmonized Tariff Code           | 8483.20.40.80   |
| Noun                             | Bearing   |
| Keyword String                   | Pillow Block  |
| Manufacturer URL                 | <a href="http://www.timken.com">http://www.timken.com</a> |
| Manufacturer Item Number         | SDAF 22630  |
| Weight / LBS                     | 395   |
| B                                | 7.5 Inch   190.5 Millimeter                               |
| d                                | 5.188 Inch   131.775<br>Millimeter                        |
| D                                | 9.75 Inch   247.65<br>Millimeter                          |
| Actual Bolt Center to<br>Center  | 0 Inch   0Millimeter                                      |
| Bolt Spacing Maximum             | 23.625 Inch  <br>600.075Millimeter                        |
| Bolt Spacing Minimum             | 20.875 Inch  <br>530.225Millimeter                        |
| Nominal Bolt Center to<br>Center | 22.3 Inch   565.2 Millimeter                              |
| Diameter S-1                     | 5 3/16 in   |
| A                                | 7.50 in   |
| B                                | 26.7500 in  |
| C                                | 9.3750 in   |
| D                                | 2.7500 in   |
| E Max.                           | 23.6250 in  |
| E Min.                           | 20.8750 in  |
| F                                | 5.875 in  |
| H <sup>1</sup>                   | 15.1875 in  |
| Oil Level K                      | 2.8750 in   |
| L <sup>2</sup>                   | 9.7500 in   |
|                                  |   |



## LUOYANG MONTON BEARING SCIENCE & TECH...

|                                      |                  |
|--------------------------------------|------------------|
| Y                                    | 3.2656 in        |
| No. of Base Bolts Required           | 4                |
| Size of Base Bolts Required          | 1.25 in          |
| Adapter Assembly Number <sup>3</sup> | SNW-130 x 5-3/16 |
| Housing Only <sup>4</sup>            | SDAF630          |
| Bolt Hole Length                     | 2.625 in         |
| Bolt Hole Width                      | 1.250 in         |
| Assembly Weight                      | 395 lb           |
| Triple Seal 2 Req ' d                | LOR 125          |
| Full Timken Part Number              | SDAF22630        |